

FLIGHT SUMMARY REPORT

Flight #: 91-155
Date: 26 August 1991
Sensor Package: Hycon HR-732
Wild-Heerbrug RC-10
Area(s) Covered: Sierra Nevada

Investigator(s): Weber, USDA
Flight Request: 91R104

Aircraft #: 706
Julian Date: 238

SENSOR DATA

| | | |
|-----------------------|---|---|
| Accession #: | 04286 | 04287 |
| Sensor ID #: | 038 | 034 |
| Sensor Type: | HR-732 | RC-10 |
| Focal Length: | 24" 609.6 mm | 12" 304.66 mm |
| Film Type: | High Definition Aerochrome IR SO131 | High Definition Aerochrome IR SO131 |
| Filtration: | cc.10B | cc.20B |
| Spectral Band: | 510-900 nm | 510-900 nm |
| f Stop: | 8 | 4 |
| Shutter Speed: | 1/75 | 1/125 |
| # of Frames: | 225 | 339 |
| % Overlap: | 60 | 60 |
| Quality: | Excellent | Excellent |
| Remarks: | | |

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and *in situ* data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides descriptions of the camera systems flown onboard the ER-2s.

Camera Systems

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrug RC-10 metric mapping camera
 - 9 x 9 inch film format
 - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
 - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
- Hycon HR-732 large scale mapping camera
 - 9 x 18 inch film format
 - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet
- IRIS II Panoramic camera
 - 4.5 x 34.7 inch film format
 - 24 inch focal length lens
 - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for NASA-Ames aircraft acquired photographic and digital imagery. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: (605) 594-6151).

Additional information regarding ER-2 acquired photographic and digital data is available through the Aircraft Data Facility at Ames Research Center. For specific information regarding flight documentation, sensor parameters, and areas of coverage contact the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: (415) 604-6252).

CAMERA FLIGHT LINE DATA
FLIGHT NO. 91-155

Accession # 04286
 Sensor # 038

| Check Points | Frame Numbers | Time (GMT-hr, min, sec) START | Time (GMT-hr, min, sec) END | Altitude, MSL feet/meters | Cloud Cover/Remarks |
|--------------|---------------|----------------------------------|--------------------------------|------------------------------|--|
| A - B | 0001-0052 | 20:58:55 | 21:11:15 | 65000/19800 | 10% scattered cumulus (frames 0050-0052) |
| C - D | 0053-0094 | 21:16:45 | 21:26:40 | " | 10% cumulus (frame 0053); very thin cirrus (frame 0073, 0081-0083, 0092) |
| E - F | 0095-0116 | 21:32:39 | 21:37:39 | " | Clear |
| G - H | 0117-0165 | 21:48:55 | 22:00:32 | " | 10-20% scattered cumulus (frames 0163-0165) |
| I | 166 | 22:04:25 | ----- | " | 20% scattered cumulus |
| J - K | 0167-0225 | 22:11:19 | 22:25:22 | " | Clear |

**CAMERA FLIGHT LINE DATA
FLIGHT NO. 91-155**

Accession # 04287

Sensor # 034

Page 1/2


| Check Points | Frame Numbers | Time (GMT-hr, min, sec) | | Altitude, MSL feet/meters | Cloud Cover/Remarks |
|---------------------|----------------------|--------------------------------|------------|----------------------------------|--|
| | | START | END | | |
| A - B | 3720-3726 | 17:54:52 | 17:57:42 | 65000/19800 | Clear |
| C - D | 3727-3739 | 18:04:11 | 18:09:54 | " | Clear |
| E - F | 3740-3756 | 18:15:56 | 18:23:36 | " | Clear |
| G - H | 3757-3780 | 18:28:37 | 18:39:38 | " | Clear |
| I - J | 3781-3804 | 18:45:53 | 18:56:54 | " | 10% cumulus (frames 3793-3801) |
| K - L | 3805-3835 | 19:07:20 | 19:21:42 | " | 10% cumulus (frames 3813-3814, 3816-3817); 10-30% cumulus (frames 3820-3831) |
| M - N | 3836-3860 | 19:27:53 | 19:38:59 | " | 10-20% cumulus (frames 3852-3860) |
| O - P | 3861-3895 | 19:47:56 | 20:03:40 | " | 10% cumulus (frames 3861-3863, 3870-3871, 3877-3878) |

CAMERA FLIGHT LINE DATA
FLIGHT NO. 91-155

Accession # 04287
 Sensor # 034


Page 2/2

| Check Points | Frame Numbers | Time (GMT-hr, min, sec) START | Time (GMT-hr, min, sec) END | Altitude, MSL feet/meters | Cloud Cover/Remarks |
|--------------|---------------|----------------------------------|--------------------------------|------------------------------|--|
| Q - R | 3896-3923 | 20:12:07 | 20:24:37 | 65000/19800 | 10% cumulus (frames 3915-3916); 10-30% cirrus and cumulus (frames 3918-3923) |
| S - T | 3924-3942 | 20:45:47 | 20:54:22 | " | 10% cumulus (frames 3924-3925, 3932-3933) |
| U - V | 3943-3969 | 20:59:52 | 21:12:06 | " | 10-20% cumulus (frames 3968-3969) |
| W - X | 3970-3990 | 21:17:40 | 21:27:10 | " | 10% cumulus (frames 3970-3973); thin cirrus (frames 3979-3981); 10-20% cirrus (frames 3984-3985) |
| Y - Z | 3991-4001 | 21:33:30 | 21:38:16 | " | Clear |
| 1 - 2 | 4002-4027 | 21:49:52 | 22:01:30 | " | 10% cumulus (frames 4025-4027) |
| 3 | 4028-4028 | 22:05:21 | 22:05:21 | " | 20% cumulus |
| 4 - 5 | 4029-4058 | 22:12:17 | 22:26:02 | " | Clear |



-124: 31

FLIGHT 91-155 DUAL HR-732 / RC-10 26 AUGUST 1991 A/C 706
 OVERLAY FOR %CWUSA LAMBERT CONFORMAL PROJECTION: SP1 = 36.3 SP2 = 39.9 CM = -120.9 ROTATED BY 0.0
 17:30:35 TO 23:11:25 UT SCALE = 1: 2.69E+06 TIME TICS EVERY 5.00 MINUTES



FLIGHT 91-455


25 August 1991

A/C 706

HR-732

Accession # 04286

JNC-43



26 August 1991

FLIGHT 91-155

FC-10

Accession # 04287

JNC-43